

F-16 Combat Pilot

Spectrum, Amstrad CPC, Commodore C64/C128

Introduction

Welcome to the world of the F-16 combat pilot. In this award-winning flight simulation you will experience the thrills of flying one of the world's most advanced multi-role combat aircraft on missions ranging from air-to-air interception to battlefield attack. In addition to single missions F-16 Combat Pilot allows you to participate in Operation Conquest - a multi-mission strategic conflict involving real-time interaction between aircraft, ground forces and military installations. Your experience as an F-16 pilot begins in the first of eight squadrons. Each squadron has a combat zone of roughly 20,000 sq. miles.

Loading Instructions

Commodore 64/128 Cassette: Hold SHIFT & RUN/STOP keys and press PLAY. Disc: Type LOAD""",8,1. Connect joystick to port 2 and use joystick to select options.

Spectrum Cassette: LOAD""". Disc: Enter.

Amstrad CPC Cassette: Ctrl + Enter. Disc: RUN"F16.

Cassette versions must first be loaded from side A or side 1. n.b. Two joystick option on Spectrum: In addition to having pitch and roll control as usual on one joystick, it is possible to operate throttle and rudder control on a second joystick.

Keyword protection

After loading the program and selecting the appropriate language, you will be prompted to enter a security keyword from the table attached. Simply find the word that corresponds

to the page, paragraph and word number and type it in, followed by enter.

Controls

Spectrum **C64**

Amstrad

Roll right * → Right*

Roll left * ← Left*

Pitch up * ↓ Back*

Pitch down * ↑ Fwd*

Rudder right X** X

Rudder left Z** Z

Increase throttle Q** +

Decrease throttle A** -

Undercarriage U U

Wheelbrakes/Airbrakes B B

Jettison fuel tanks K + Shift J and F

Jettison all J + Shift J and A

Eject E + Shift Ctrl E

Displays

Radar target select S <

MFD select D** 1,2,3,4

HUD on/off H H

Weapons

Weapons select W F1

Chaff C F5

Flares F F7

Fire weapons Space* FIRE

UFCP

Autopilot L Ⓞ

Recce pod transmit R R
Mode select M M
Channel select N C
Pause/continue P P

* JOYSTICK 1

**JOYSTICK 2 (SPECTRUM)

Spectrum - the program defaults to using a Sinclair joystick plugged into port 1. If you wish to fly using the cursor keys then select cursor control by pressing key 1. If you wish to use the Kempston joystick press key 1 again. It is important to select the correct control otherwise you will not be able to load weapons onto the aircraft.

Mission selection screen

Each side of the pentagon represents a mission category:
Scramble - air-to-air interception. Objective - intercept and destroy two incoming enemy fighters, then return to base.
Hammerblow - offensive counterair operations. Various ground attack missions against military targets including airfields, military bases, command centres, early warning radar installations, SAM and AAA sites. Objective - destroy assigned targets and return to base.

Deepstrike - ground attack on strategic installations including fuel depots, power stations and factories. Objective - destroy assigned targets and return to base.

Tankbuster - battlefield close air support. Objective - locate and destroy tank battalions and return to base.

Watchtower - reconnaissance. Objective - fly over designated targets, transmit data back to HQ using ATARS pod and return to base.

Operation Conquest - in the centre of the pentagon is the icon to select the strategic campaign. This option is not available until you have successfully flown a mission in each category. (n.b. This does not apply to C64 cassette users since they do not have a pilot's log facility.) The objective is to destroy sufficient enemy installations and aircraft in order to force him into surrender. This will take several missions during which the enemy will also be trying to force the allies to surrender. After each successful campaign you will be promoted to the next squadron.

Training - the enemy will not fire at you when this option is ON. Selection of mission category is as before.

Quickstart - bypasses the preflight briefing and weapon selection. Your aircraft is loaded with a general purpose weapon mix and no waypoints are loaded into the navigation computer.

Pilot's Log - records successful missions and your squadron level. Make sure that you open a new pilot's log before your first flight or load your old pilot's log. This feature is not available on C64 cassette. For C64 disc users, you will need to have preformatted a blank disc using the following command:

OPEN 1,8,15,"n:LOG,EA"

Spectrum and Amstrad cassette and disc users - follow on-screen prompts.

Exit - move to pre-flight briefing

Pre-flight briefing

Here you will be given your mission objective and target coordinates (not in Scramble). You will also be able to select your flying conditions i.e. clear or cloudy, day or night (not available on C64).

To plan your flight, set your waypoints to match the target coordinates. This is achieved by moving the cursor to the required map location and pressing fire. Waypoints are automatically preloaded on the Spectrum and Amstrad versions. Waypoint 0 is always set to your take-off position. The various symbols on the map correspond to the target types described above.

Weapon Loading
After the pre-flight briefing you will see the weapon loading screen. For any of the five single mission categories e.g. Scramble, etc., you may load your weapons by moving the cursor to the crew's choice and pressing the fire button. All weapons may be removed from the aircraft by selecting "clean". If you wish to load up weapons of your own choice, first move the pointer to the required weapon name e.g. AIM-120, AGM-65E etc, and press the fire button. The weapon name will appear at the top of the screen with the number of the weapon type loaded. Move the cursor to approximately a quarter of an inch underneath the weapon loading point and press the fire button again. The weapons should appear, loaded symmetrically on the aircraft. Further weapons may be loaded by repeating this procedure. If the weapons do not appear try moving the cursor position slightly. Note that the heavier weapons may only be loaded on the inner pylons. The gun, internal fuel and Lantirn are always preloaded. External fuel tanks and the ATARS pod are loaded without having to point to the loading position.

During Operation Conquest the crew's choice option does not function since the crew will not be aware of your objectives. Load your weapons manually.

Weapon types:
AIM-120 AMRAAM - radar-guided medium range air-to-air missile. Maximum range 30 miles.
AIM-9M Sidewinder - infra-red short range air-to-air missile. Maximum range 11 miles. (Both of the above missiles can only be used with the air radar active and the lock-on diamond visible on the HUD.)
AGM-88A HARM - radar-guided anti-radiation missile for use against EWR sites.
AGM-65D Maverick - infra-red air-to-ground missile for use against tanks.
AGM-65E Maverick - laser-guided air-to-ground missile for use against all ground targets except runways.

The Lantirn system will automatically acquire each ground target as it comes into range. As soon as the lock-on diamond appears, fire the missile. Mavericks and HARM can only be used with the ground radar on and the lock-on diamond active.
Durandal - anti-runway bomb. Drop within enemy airfield to destroy runway.
External fuel tank - up to 3 may be carried if the ATARS pod is not fitted.
ATARS - reconnaissance pod - can be fitted only on the centre line hardpoint.
LANTIRN - night vision & laser guidance system - always fitted.
Internal cannon - always fitted - 500 rounds max. Range approximately 0.5 miles. Only used for air-to-air dogfights.
Chaff & flares - 30 of each fitted for use as decoys against incoming missiles. Active only for short period - roughly 30 seconds.

Leave the weapon loading screen by selecting Exit.

Flight - getting airborne and landing.
Take-off:
Once you are in the cockpit begin by opening the throttle to 100% (hold down the Q key on Spectrum and Amstrad or + key on the C64). Release the key and press again to activate reheat (maximum thrust). As your speed approaches 150 kts, pull back on the joystick (or cursor key) to raise the nose of the aircraft and take-off. Remember to raise the undercarriage shortly after take-off otherwise it will be damaged and remain in the down position.

Flying to a target:
Select your required waypoint on the Up Front Control Panel (UFCP) and turn your aircraft until your heading matches the bearing of the waypoint. To achieve the maximum turn rate, bank your aircraft onto a wing tip and pull on the joystick (elevator control). This technique is particularly important during a dogfight when you will be avoiding enemy missiles and using chaff and flares. n.b. If you pull or push g for long periods you will "black out" and "red out" respectively. You will regain consciousness in a few seconds.

In order to get lined up correctly a common technique is to adjust your aircraft heading so that it is approximately double the airfield bearing e.g. if the airfield bearing is 40, fly on a course of approximately 80, or if the airfield bearing is 330, fly on a course of 300. As you get nearer to the airfield you should see the bearing gradually change towards 360. Continue to adjust your heading to roughly twice the bearing by turning slowly towards the airfield e.g bearing of 20 and a heading of 40, a bearing of 10 and a heading of 20, and so on. As the bearing continues to approach 360 so will your heading and the

result should be both heading and bearing equal to 360 and you are lined up with the runway. The same principle applies for a landing due South, with heading and bearing of 180.

Give yourself plenty of time by performing this manoeuvre at over 10 miles from the runway. If you have already reduced the throttle to 80% and lowered the undercarriage your speed should be between 120 and 140 knots which is a typical approach speed. Use your airbrake if your speed is too high. It is also important to adjust your altitude to approximately 2500 feet. Keep the nose of the aircraft approximately 5° above the horizon and this will ensure a good approach speed and a rate of descent of roughly 11 feet per second. If you find that you are running out of altitude, open the throttle slightly and this will reduce the rate of descent. Attempting to adjust your rate of descent with pitch angle will cause major fluctuations in speed or even a stall and will probably lead to crashing as you overcorrect for errors. Use the ILS display as described below to ensure a good approach. Just prior to touchdown pull the nose of the aircraft up very slightly (flare) to reduce the rate of descent to less than 10 feet per second. It is possible to land with the wheels up but only if the undercarriage is damaged. Your VSI will have to be less than 5 feet per second. After touchdown, reduce the throttle setting to 60% (minimum) and apply the brakes by holding down key B until the aircraft stops.

Autoland option:
During your approach to land at an airfield, you may select the autoland feature providing that the ILS display is active and the localiser and glideslope needles are displayed. Follow the

advice above until the localiser and glideslope needles appear on the ILS display and then select autopilot (key L on Spectrum and Amstrad, key Ⓞ on the C64). The autopilot will confirm that it has control and it will steer your aircraft towards the runway. Be prepared to take over control just prior to touchdown in order to flare and reduce your rate of descent. Continue to monitor your approach as the autopilot is not infallible.

One last point. If you get into serious trouble you can always eject.....

Debrief
After landing (or crashing!) you will see the debrief screen with a summary of your performance during the mission. If appropriate, you will be given your Kill Ratio (KR) and your Mission Effectiveness (ME).

KR = total number of targets destroyed/ number of weapons used

ME = number of assigned targets destroyed/total number of assigned targets

After your debrief you will return to the Mission Selection pentagon screen.

result should be both heading and bearing equal to 360 and you are lined up with the runway. The same principle applies for a landing due South, with heading and bearing of 180.

Give yourself plenty of time by performing this manoeuvre at over 10 miles from the runway. If you have already reduced the throttle to 80% and lowered the undercarriage your speed should be between 120 and 140 knots which is a typical approach speed. Use your airbrake if your speed is too high. It is also important to adjust your altitude to approximately 2500 feet. Keep the nose of the aircraft approximately 5° above the horizon and this will ensure a good approach speed and a rate of descent of roughly 11 feet per second. If you find that you are running out of altitude, open the throttle slightly and this will reduce the rate of descent. Attempting to adjust your rate of descent with pitch angle will cause major fluctuations in speed or even a stall and will probably lead to crashing as you overcorrect for errors. Use the ILS display as described below to ensure a good approach. Just prior to touchdown pull the nose of the aircraft up very slightly (flare) to reduce the rate of descent to less than 10 feet per second. It is possible to land with the wheels up but only if the undercarriage is damaged. Your VSI will have to be less than 5 feet per second. After touchdown, reduce the throttle setting to 60% (minimum) and apply the brakes by holding down key B until the aircraft stops.

Autoland option:
During your approach to land at an airfield, you may select the autoland feature providing that the ILS display is active and the localiser and glideslope needles are displayed. Follow the

